

# Antifreeze Reference Chart



	Conventional	Extended Life	Universal Extended Life	Heavy Duty Non-Nitrited
Formulation	Inorganic Additive Technology	ELC/ Organic Acid Technology	Hybrid Organic Acid Technology	Organic Acid Technology NAPS Free
Color	Green	Clear	Yellow	Red
Base	EG	EG	EG	EG
Best Use	Most Automobiles and Heavy Duty Truck/ Equipment	Newer Automobiles and Light Duty Gasoline Trucks	Virtually Any Vehicle	Heavy Duty Trucks
Change Interval	30,000 miles	5 Years/ 150,000 miles	60,000 Miles	5 Year/ 150,000 Miles
Nitrites	Yes	None	Yes	None
Phosphates	None	None	None	None
Silicates	Low	Low to None	Low to None	None
Corrosion Protection	Yes	Yes	Yes	Yes
Freeze Point	-38.9°F	-38.9°F	-38.9°F	-38.9°F
Boil-Over Temperature	226°F	226°F	226°F	226°F
pH Level	10-11	10-11	10-11	10-11
Product Warranty	Yes	Yes	Yes	Yes

## Ready-to-Use Blends Available



Manufactured at  
221 Dalton Ave  
Charlotte, NC 28206